

EEWI Series

2KVA Pure Sine Wave Power Inverter Off-grid Single Phase



Applications

- Application in wind, Solar, Wind&Solar hybrid power generation station.
- Application in household wind&solar hybrid power generation system.
- Power supply for those unmanned regions like the coastal islands, remote mountainous regions and border posts.

Features

- Can be applied in wind, solar, wind&solar hybrid power generation system.
- Simple structure, complete function
- Low no-load loss by using industrial frequency transformer
- CE certification

Technical Parameters

Model	EEWI20-48	EEWI20-120
DC Input Parameters		
Rated battery voltage	48Vdc	120Vdc
Input overvoltage point	68Vdc	170Vdc
Input overvoltage recovery point	66Vdc	165Vdc
Input undervoltage point	43.2Vdc	108Vdc
Input undervoltage recovery point	48Vdc	120Vdc
AC Output Parameters		
Output phase number	Single phase	
Rated output power	2KVA	
Rated output voltage	110/120/220/230/240Vac	
Rated output frequency	50/60±0.5HZ	
THDi	<5%	
Efficiency		
Max. conversion efficiency	≥85%	

Protection Functions	
DC input overvoltage /undervoltage protection	YES
DC reversed connection protection	YES
AC output overload protection	YES
AC short circuit protection	YES
Surge protection	YES
Over-temperature protection	YES
General Parameters	
Display mode	LCD
Display information	Battery voltage, inverter voltage, inverter current, inverter power, and working status of battery overvoltage/.undervoltage and AC output overload/short circuit.
Isolation mode	Industrial frequency isolation
No-load current	≤0.6A ≤0.3A
Ambient temperature	-20℃ ~ +40℃
Humidity	5%~95%, No condensing
Noise	<60dB
Cooling mode	Natural cooling
Cover protection class	IP20
Product dimension (W*H*D)	235*352*400mm
Product net weight	20kg
Note: the listed specs are just for your reference	