

Vertical axis wind turbine generator **Technical Datasheet**

Part No: EN-2KW-Q5

Description: The permanent magnetic EN-2KW-Q5 wind turbine is combined by savonius and darrieus turbines, has high-efficient energy output, is the most compact, quiet, rugged and reliable vertical axis small wind turbine. The EN-2KW-Q5 wind turbine is widely used in LED lighting system, signal & camera security, telecommunication field for off-grid residence. The EN-2KW-Q5 wind turbine is extremely easy to integrate with solar panels to create off-grid power systems that require modest amounts of energy. Available in 48V,96V for battery.

(F

Design


- 1) The EN-2KW-Q5 is the best & reasonable combination of savonius and darrieus wind turbine generator.
- 2) The EN-2KW-Q5 is designed on a unique low inertia axial flux generator which utilizes Neodymium permanent magnetic material.
- The E EN-2KW-Q5 has zero cogging with its highly efficient, allow the turbine to generate power at very low wind speeds and 3) deliver a high output in working wind speeds.
- The EN-2KW-Q5 can survive from winds up to 45m/s by a passive aero-dynamic design that reduces turbine RPM and power_ 4) output at a certain threshold.
- The robust aluminum alloy chassis and stainless steel components are protected by the aerospace grade coatings and anodizing. 5)

Advantage



Feature

EN-2KW-Q5 wind turbine	
Turbine diameter	: 2.5 meter
Turbine height	: 2.4 meter
Rotor Type	: Vertical savonius & darrieus combination
Blade Material	: Casting aluminum alloy
Rated output	: 2000w at 13m/s
Peak output	: 2100W
Cut-in speed	: 3m/s
Voltage	: 48V, 96V



* Wind turbine performance is subject to many factors. All output data contained in this document is indicative and actual turbine outputs will depend on the prevailing site and installation conditions

> ENGELEC ENERGY Intelligent manufacturing, Industry 5.0 Email:info@engelec.cn www.enaelecenerav.com