

Vertical axis wind turbine generator EN-3KW-H Technical Datasheet

Part No: EN-3KW-H

Description: The permanent magnetic EN-3KW-H wind turbine blades is straight like "H" type, It has

high-efficient energy output, is the most compact, quiet, rugged and reliable vertical axis small wind turbine. The EN-3KW-H wind turbine is widely used in LED lighting system, signal & camera security, telecommunication field for off-grid residence. The EN-3KW-H wind turbine is extremely easy to integrate with solar panels to create off-grid power systems that require modest amounts of energy. Available in 96V, 120V for battery charging applications.



Design

- 1) The EN-3KW-H is low start up wind speed, low compact, beautiful, easy installation and low vibration.
- 2) The EN-3KW-H is designed on a unique low inertia axial flux generator which utilizes Neodymium permanent magnetic material.
- 3) The EN-3KW-H has zero cogging with its highly efficient, allow the turbine to generate power at very low wind speeds and deliver a high output in working wind speeds.
- 4) The EN-3KW-H can survive from winds up to 40m/s by a passive aero-dynamic design that reduces turbine RPM and power output at a certain threshold.
- 5) The robust aluminum alloy chassis and stainless steel components are protected by the aerospace grade coatings and anodizing.

<u>Advantage</u>



Self Start

Straight blades, breeze start, low cogging torque at 2.0 m/s

Quie

Low noise, < 40dB above background

Reliable

Precision Aerodynamic design from aircraft-engineering

Rugged

Durable, withstands storm force winds up to 35m/s

High output

Stright blades, high efficiency.

Features

EN-3KW-H wind turbine

Wheel diameter : 2.85 meter

Rotor Type : Vertical straight blades

Blade Material : Strong glass fiber
Rated output : 3000W at 12m/s

Peak output : 3500W

Cut-in speed : 2..0 m/s

Wheel height : 3.5 meter

Rated voltage : 96V, 120V



Wind turbine performance is subject to many factors. All output data contained in this document is indicative and actual turbine outputs will depend on the prevailing site and installation conditions.

ENGELEC ENERGY

Intelligent manufacturing, Industry 5.0 Email:info@engelec.cn www.engelecenergy.com Call at +86 13505876536